



devolo

dLAN 1000 mini

Technical data

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az Auto MDI/X
Protocols	CSMA/CA (Powerline)
Transmission speeds	Ethernet 10/100 (mbps) Powerline 200/500/600/1000 (mbps)
Modulation • Carrier	Powerline OFDM - 4096/1024/256/64-QAM, QPSK, BPSK • Powerline 2880
Range (in m)	Powerline: 400
Security	128 Bit AES
LEDs	dLAN (multi)
Buttons	Pairing
Socket • Connector • Countries	(none) • Type E+F (CEE 7/7) • (FR,BE,PL,CZ,SK,DE,NL,ES,PT,AT,SE,FI,NO,GR,HU,SI)
Device port	1 x Ethernet RJ45
Power consumption	Maximum W/A: 4.2W Typical W/A: 3W Stand-By W/A: 0.8W
Power supply	internal 196-250 V AC 50-60 Hz
Temperature (Storage • Operating)	-25°C to 70°C • 0°C to 40°C
Dimensions (in mm, without plug)	82 x 67 x 29
Ambient conditions	10-90% Humidity (non-condensing)
Operating systems	Windows 7 (32 Bit), Windows 7 (64 Bit) Windows 8.x (32 Bit), Windows 8.x (64 Bit), Windows 8.x Pro (32 Bit), Windows 8.x Pro (64 Bit), Windows 10.x Pro (32 Bit), Windows 10.x Pro (64 Bit) Ubuntu-Linux 14.04 (32 Bit), Ubuntu-Linux 14.04 (64 Bit) MAC OS X 10.9, MAC OS X 10.10, MAC OS X 10.11, MAC OS X 10.12
Certifications	CE Class B (EU, CH, NO)

Sales information

Warranty (in years) 3



devolo

Accessories

Printed Install Flyer
Ethernet Cable(s)

Single adapter

8146 (EU)

EAN: 4250059681460
Weight: 300 g
Dimensions: 190 x 118 x 80 mm

WEEE additional information:

Weight WEEE: 170 g
Paper (Green Dot): 110 g
Plastic (Green Dot): 2 g
other (Green Dot): 0.2 g

Starter Kit

8153 (EU)

EAN: 4250059681538
Weight: 520 g
Dimensions: 119 x 231 x 80 mm

WEEE additional information:

Weight WEEE: 340 g
Paper (Green Dot): 165 g
Plastic (Green Dot): 4 g
other (Green Dot): 0.4 g